

MODEL	PDSF375DP-6B5 (7 Bar)
COMPRESSOR	
Type	Rotary Twin Screw, Single-Stage Oil-cooled
Free Air Delivery (m ³ /min)	11.3
Rated Operating Pressure MPa (kgf/cm ²) [psi]	0.7 (7.14) [102]
Compressor Oil Capacity (L)	40
Air Outlet Valve	3/4"x2, 2"x1
ENGINE	
Make/Model	KUBOTA V3800DI-TI-E2B-COHE1
Type (4 Cycle. Water-Cooled)	Direct-Injection Turbo-Charged Intercooled
Rated Output PS (kW) / rpm	102.2 (75.2) / 2600
Engine Oil Capacity (L)	13
Fuel Tank Capacity (L)	178
Battery	130F51 x 1
DIMENSION & WEIGHT	
Overall Length mm (inch)	3665 (144.3)
Overall Width mm (inch)	1975 (77.8)
Overall Height mm (inch)	1773 (69.8)
Dry (Operating) Weight (kg)	1780 (1980)
Tire Size	6.50-14 SPRx2W
OTHER	
Sound Power Level in Decibels (dB)	100
Sound Pressure Level dB (A)	71
Designated Emissions Regulation	JPN Stage 2